
CRU2R //X

Diesel System Test Bench

The Affordable Diesel Specialists CRDi Solution

Service Station for All Makes Passenger Car, Light
and Medium Duty CRDi systems.

2500 Bar

**Standalone Air-Driven
Test Bench for 1 Diesel
CRDi Injector.**



**Authorized Solution
for Continental/VDO**



SPECIALISTS

CRDi

EUI/EUP

HEUi

CRP

ENGINE

GDi

EFi

GDi Pumps

Overview of the CRU2.R-X

Precise, repeatable and rapid Diesel Injectors Testing

[1] Injector Testing & Coding*

- 6-12 minutes testing and coding* time per injector
- CRi / CRiN injectors (All Brands and Types).
- Capable for all EU6 technologies such as VCC and NCC technology, iART, PCRS5, XPI and more...


CGL - Authorized Continental / VDO "Blind-Lift"
Measurement of Piezo-Stack

CloudX™

Powerful innovations at your fingertips with Carbon Zapp CloudX computing Platform. Take complete control over your service benches with cloud-based Apps, business intelligence (BI) services and database management systems over a secure Internet connection.



CRDi Test Bench for Diesel Specialists & Workshops



Passenger & Light Duty Systems

AZO SOFTWARE



Features

- A Continental/VDO Authorized Test Bench
- Xtremely Fast Testing Times without any Compromise
- Modern Design for every Service Station
- Optimized Working Area to reduce Injector Set-up Times
- 2500Bar Operating Pressure
- EU6 Systems Testing and Coding

CloudX Capabilities

- Coding capability for all brands and types available in the market today. Bosch, Denso, Delphi, Continental / VDO, CAT
- Off-Highways CR applications testing and coding* (John Deere, Komatsu, Hino, Isuzu)
- Cummins XPI*, Caterpillar-Perkins C4/C6 and other Medium-Duty testing and coding

Diesel CRDI testing and coding

Ergonomic, Fast and Easy Injector Clamping device to minimize mounting times.

Fully Adjustable height for all types of CR injectors.

Utilizes a spring-loaded injector holder to ease the operation of the user.

Advanced self air-cooling system to optimize long term nonstop operation at all environmental conditions.

Live Response Time Measurement for all injectors

BIP Actuation Measurement for all Heavy-Duty type solenoids

Adaptability for every type of Diesel Injectors in the market

Continuous Database updates and new Software capabilities to meet the market needs.

Android Powered 10 HMI with unlimited flexibility and connectivity competencies.


Injector flushing feature pre-installed (optional kit available)

*New database and Coding is continously being updated to new EU6 applications

SPECIALISTS



TESTING WITH ILLUMINATED
SPRAY CHAMBER.



TESTING WITH RESPONSE MEASUREMENT
CHAMBER FOR CODING.

CRDi
EUI/EUP
HEUi
CRP
ENGINE
GDi
EFI
GDi Pumps

CRU2R //X Specifications

DESCRIPTION		UNIT	CRU.2R X (CZ-008728)
Machine Dimensions	Length	mm	620
	Width	mm	780
	Height	mm	740
Weight		kg	63
HMI	Tablet Touchscreen	Inches	10
Internet Update	WiFi / Ethernet	-	YES / YES
Pressure Source	Type	Air Driven High Pressure Pump	
Test Oil	Type	"(DxL-ISO) ISO4113 Calibration Oil"	
Test Oil Tank	Capacity	Liters	4
Max Pressure	Pressure	Bar	2500
Max RPM	Max Revolutions Per Minute	RPM	-
Max Pumps	Pumps Test	Slots	-
Max Injectors	Test Injectors	Slots	1
HP Pump	High Pressure Pump	Type	Pneumatic Pump
LP Pump	Supply Pressure	Bar	-
	Pressure	Bar	6.5-10
Air Supply	Air Tank Capacity	Lt	250
	Air Flow	Lt/ Min	400
	Min Diameter at Air Supply Hose	mm	8
	Air	Type	Water / Oil FREE
Main Power Supply	Phases	Number	1
		TYPE	1P+N
	Voltage	VAC	100 - 240
	Frequency	Hz	50/60
	Current	Ampere	5
	Max Consumption	kVA (100V/240V)	0.5 / 1.2
Operating Temperature	Min / Max Room Temperature	Celsius	6 / 35
IVM Sensors	Measurement Sensors	Type / Quantity	XKM / 2 *

EXPLANATIONS

- : N/A
 - A: Air Cooling
 - W: Water Cooling
- PRESSURE SOURCES**
 Air Driven High Pressure Pump
 Air Motor Driven High Pressure Pump
External: Pressure coming from another Test Bench or external source
Electr. Pump: Fuel Injection system or Industrial Application Electrical Pump 12VDC
 -: No Pressure Source

MEASUREMENT SENSORS

- XKM [Dynamic Meas. Sensor]; High Accuracy: ± 0.1%, Exceptional Repeatability ±0.05%.
 - Measur. Range: 1-1000ml/min
 - DFM 500 [Dynamic Measurement Sensor]; Accuracy: ± 1%, Repeatability 0.5%, Measurement range: 5-500l/min
 - DFM 50 [Dynamic Measurement Sensor]; Accuracy: ± 1%, Repeatability 0.5%, Measurement range: 0.5-50l/min
 - Volumetric Tubes [Static Analog Measurement]; Accuracy: 1mi., Measurement range: 0.5-65ml
- APPLICATIONS**
 Passenger Car/ Motorcycles: Volumes up to 120mm³/H
 Light Duty: Volumes up to 200mm³/H
 Medium Duty: Volumes up to 300mm³/H

eXpanding Capabilities

X Series 2023

Space saving, accessory organizers for everyday tasks.
Increased productivity and uncluttered space.

Extras MTBR-X & PTBR-X



1 Desk & Harness Shelf



Hydraulic Hose Side Panel Pocket with Drain

2



Ultrasonic Shelf

for GTBR-X,
ITBR-X, HTBR-X





**Carbon Zapp Trolley
Fully Configured Setup**



CZ Base Trolley



**Hose & Harness
Side Organizer**
(max. 2 pcs per trolley)

Carbon Zapp Trolley

Ideal workshop organizer to fit most parts of the machine like harnesses, hoses, adapters, tools and flanges. Can be easily transformed to a Cambox and/or pump rack for easy transfer and storing.



**CRp Flange Drawer
Organizer**
(max. 1 pc per trolley)



**Cambox/Pump
Transfer Rack**
(max. 2 pcs per trolley)





CloudX is CarbonZapp IoT Cloud computing Platform

Powerful innovations at your fingertips
with CZ CloudX computing Platform

CZ CloudX computing technology Platform as a service (PaaS) is a complete environment in the cloud, with resources that enable clients the full control of their Bench with cloud based Apps access them over a secure Internet connection. With middleware, development tools, business intelligence (BI) services, database management systems and more.

CloudX allows clients to access live online updates of database, remote operation and status report of their bench. Generate remote reports for handling, printing, filling and organizing from machine database. Instant activation of features on a pay-as-you-go basis. Multiple machines management support. Complete machine cloud back-up and instant trouble shooting via X-Connect directly from CZ factory. Receive notifications on your smart devices for machine maintenance tasks like Oils, Filters, Service, and more.

Explore today new powerful innovations at your fingertips with CZ CloudX computing Platform.

CloudX Features

- IoT Cloud computing Platform. Industry 4.0 Complaint
- Instant Activation of Features on a pay-as-you-go basis
- Live Online Updates of Database and supporting new requests from clients
- Multiple machines management
- Remote Operation and Status Report of Client Bench
- Complete machine cloud back-up
- Generating remote reports for handling, printing, filling and organizing from machine database
- Instant troubleshooting via X-Connect directly from CZ Factory
- Notifications on Client smart devices for machine maintenance tasks like Oils, Filters, Service, and more



Scan CZ Digital
Product Catalog

Headquarters & Production
364 Varis-Koropiou Ave. Koropi
194 42 Athens, Greece

German Branch
A.I.S. GmbH
75438 Knittlingen, Germany

email contact@carbonzapp.com
tel +30 210 9856110
fax +30 210 9928655

carbonzapp.com