




Gasoline System Test Bench








Technologies

The professional solution for workshops to test & service **Gasoline Direct Injection Systems.**


Overview of the GDU.4R-X	SPECIALISTS
Precise & repeatable Gasoline Injectors Testing	CRDi
[4] Injectors Testing & Coding*	
 20 minutes testing and coding* time for 4 injectors 	
 GDi injectors (All Brands and Types) 	
Conventional Gasoline EFi Injectors	
Capable for all EU6 technologies	
 Coding Capable for all Types of GDi's (Energy Controlled or Volume Metering types) 	GDi
 Flushing and Servicing options for GDi injectors 	EFi
	GDi Pumps



650 Bar 4 GDi Injectors Capable

> Gasoline Direct Injection (GDi) requires high pressure testing to truly diagnose injector operation faults.





EU3 > EU6 Technologies

Features

Controls all Types and Makes of Injectors. Includes OEM Database and Test Plans

Low Pressure Testing for Conventional MPFi or Racing application Injectors 0-10Bar

Controls NEW Generation High Pressure GDi with multiple Step Current profiles

LPG for Heavy Duty Applications (Trucks, Commercial Vehicles)

Continental / Siemens GDi injectors (EU5) testing only with approved Energy Control

Nozzle reaction time measurement for all systems via RSP sensor

Dual System - Flushing / Cleaning system using detergents and Ultrasonics

Efficient Working Area with Protective Hood fully opening

The fastest and easiest clamping of injectors in the market

Fully Automatic and fast testing phase through a 10" Touchscreen HMI with AZO software

GDi Piezo Stack Regeneration function. The only way to correct GDi Piezo injectors after Cleaning them internally and reverse flushing them

Reverse flushing adapter and function with 25Bar pressure

Blue Limits Diagnosis for Specialists

Dynamic Electronic Mass (BK) Measurement

Prepared for Future Injector Coding

Emergency Safety Stop function



GDU4R //X Specifications

	DESCRIPTION	UNIT	GDU.4R X (CZ-008726)	
Machine	Length	mm	620	
Dimensions	Width	mm	780	
Dimensions	Height	mm	740	
Weight		kg	59	
HMI	Tablet Touchscreen	Inches	10	
Internet Update	WiFi / Ethernet	-	YES / YES	
Pressure Source	Туре	Air Driven High Pressure Pump		
Test Oil	Туре	(GxL-ISO) Calibration Oil		
Test Oil Tank	Capacity	Liters	4	
Max Pressure	Pressure	Bar	650	
Max RPM	Max Revolutions Per Minute	RPM	-	
Max Pumps	Pumps Test	Slots	-	
Max Injectors	Test Injectors	Slots	4	
HP Pump	High Pressure Pump	Туре	Pneumatic Pump	
LP Pump	Supply Pressure	Bar	-	
Air Supply	Pressure	Bar	6.5-10	
	Air Tank Capacity	Lt	250	
	Air Flow	Lt/ Min	400	
	Min Diameter at Air Supply Hose	mm	8	
	Air	Туре	Water / Oil FREE	
Main Power	Phases	Number	1	
	Phases	TYPE	1P+N	
	Voltage	VAC	100 - 240	
Supply	Frequency	Hz	50/60	
Зарріу	Current	Ampere	5	
	Max Consumption	kVA (100V/240V)	0.5 / 1.2	SNC
Operating Temperature	Min / Max Room Temperature	Celsius	6 / 35	EXPLANATIONS
IVM Sensors	Measurement Sensors	Type / Quantity	BK Coriolis / 1 *	XPL

MEASUREMENT SENSORS XKM [Dynamic Meas. Sensor]; High Accuracy: ± 0,1%, Exceptional prepatibility: 0,005%, Measur, Range: 1-1000ml/min Volumetric Tubes [Static Analog Measurement]; Accuracy: 1ml, Measurement range: 0,5-65ml APPLICATIONS Light Duty: Volumes up to 120mm3/H Light Duty: Volumes up to 200mm3/H Medium Duty: Volumes up to 300mm3/H Heavy Duty: Volumes up to 550mm3/H Medines: Volumes up to 1500mm3/H PRESSURE SOURCES Air: Air Driven High Pressure Pump Air: Air Driven High Pressure R-pump Batemati: Pressure coming from another Test Benchor External: Pressure coming from another Test Benchor effect Pump: Fuel Injection system or Industrial Application Electrical Pump 12VDC --: No Pressure Source

- : N/A

eXpanding Capabilities



Space saving, accessory organizers for everyday tasks. Increased productivity and uncluttered space.









CZ Base Trolley



Hose & Harness Side Organizer (max. 2 pcs per trolley)

Carbon Zapp Trolley

Ideal workshop organizer to fit most parts of the machine like harnesses, hoses, adapters, tools and flanges. Can be easily transformed to a Cambox and/or pump rack for easy transfer and storing.

Carbon Zapp Trolley Fully Configured Setup



CRp Flange Drawer Organizer (max. 1 pc per trolley)



Cambox/Pump Transfer Rack (max. 2 pcs per trolley)







CloudX is CarbonZapp IoT Cloud computing Platform

Powerful innovations at your fingertips with CZ CloudX computing Platform





CZ CloudX computing technology Platform as a service (PaaS) is a complete enviroment in the cloud, with resources that enable clients the full control of their Bench with cloud based Apps access them over a secure Internet connection. With middleware, development tools, business intelligence (BI) services, database management systems and more.

CloudX allows clients to access live online updates of database, remote operation and status report of their bench. Generate remote reports for handling, printing, filling and organizing from machine database. Instant activation of features on a pay-as-you-go basis. Multiple machines management support. Complete machine cloud back-up and instant trouble shooting via X-Connect directly from CZ factory. Receive notifications on your smart devices for machine maintenance tasks like Oils, Filters, Service, and more.

Explore today new powerful innovations at your fingertips with CZ CloudX computing Platform.

CloudX Features

- IoT Cloud computing Platform. Industry 4.0 Complaint
- Live Online Updates of Database and supporting new requests from clients
- Remote Operation and Status Report of Client Bench
- Generating remote reports for handling, printing, filing and organizing from machine database
- Instant Activation of Features on a pay-as-you-go basis
- Multiple machines management
- Complete machine cloud back-up
- Instant troubleshooting via X-Connect directly from CZ Factory
- Notifications on Client smart devices for machine maintenance tasks like Oils, Filters, Service, and more



Scan CZ Digital Product Catalog

Headquarters & Production 364 Varis-Koropiou Ave. Koropi 194 42 Athens, Greece **German Branch** A.I.S. GmbH 75438 Knittlingen, Germany email contact@carbonzapp.com tel +30 210 9856110 fax +30 210 9928655

carbonzapp.com